



Servo Valve Subplates and Pilot Port Tapping Plates

| | |
|---------------------------------------|----------|
| Servo Valve Cross Reference | Page 85 |
| S02 (0.625 port circle) Subplate | Page 86 |
| S03, S71 (0.780 port circle) Subplate | Page 86 |
| S72 (0.938 port circle) Subplate | Page 86 |
| S02 (0.625 port circle) Tapping Plate | Page 87 |
| S71 (0.780 port circle) Tapping Plate | Page 87 |
| S04 (0.875 port circle) Subplate | Page 88 |
| S04 (0.875 port circle) Tapping Plate | Page 89 |
| S73 (1.375 port circle) Subplate | Page 90 |
| S74 (1.750 port circle) Subplate | Page 91 |
| S06 (2.000 port circle) Subplate | Page 92 |
| S06 (2.000 port circle) Tapping Plate | Page 93 |
| S75 (2.750 port circle) Subplate | Page 94 |
| S76 Subplate | Page 95 |
| S77 Subplate | Page 96 |
| S78 Subplate | Page 97 |
| S79 Subplate | Page 98 |
| S80 Subplate | Page 99 |
| S81 Subplate | Page 99 |
| S82 Subplate | Page 100 |
| D05 Servo Tapping Plate | Page 101 |
| Mounting Hardware | Page 102 |



Servo Valve Cross Reference

| Daman pattern no. | ISO no. | Port Circle | Moog | Pegasus | Atchley | Vickers | Parker | Rexroth |
|-------------------|------------|-------------|----------------------------------|-------------------------------------|--------------------|---------|--------|------------|
| S02 | 10372-02 | 0.625 | 771 774 | 20 105H 122A | 208A 209 | SM4-10 | -- | -- |
| S03 | 10372-03 | 0.780 | -- | 132A | -- | -- | -- | -- |
| S71 | -- | 0.780 | 755 772 | -- | 200 211A 214 | -- | -- | -- |
| S04 | 10372-04 | 0.875 | 62, 730 730HP 760 760HP | 142M 142MP 162M 162MP | 215A | SM4-20 | BD15 | 4WS*2E*10A |
| S72 | -- | 0.938 | 773 | 142A 162A 162R 212, 235 | 218 | SM4-15 | -- | -- |
| S73 | -- | 1.375 | -- | -- | 225A | -- | -- | -- |
| S74 | -- | 1.750 | -- | 1330 | -- | -- | -- | -- |
| S06 | 10372-06 | 2.000 | 72 79-100 | 1282A 1282AD 1282ADL 1282B | 261 | -- | -- | -- |
| S75 | -- | 2.750 | -- | -- | 3100 | -- | -- | -- |
| S76 | -- | -- | -- | -- | -- | SM4-30 | -- | -- |
| S77 | -- | -- | 78 | 180L 180R | 240 | SM4-40 | BD30 | -- |
| S78 | -- | -- | 79-200 | 1800 | -- | -- | -- | -- |
| S79 | -- | -- | D643 | -- | -- | -- | -- | -- |
| S80 | -- | -- | -- | -- | 241 | -- | -- | -- |
| S81 | -- | -- | -- | -- | 231 242 | -- | -- | -- |
| S82 | -- | -- | -- | -- | -- | -- | -- | 4DS*1E02 |
| D03 a) | 4401-03-02 | -- | -- | 40 | -- | -- | -- | -- |
| D05 a,b) | 4401-05-04 | -- | 631 641 651 | -- | -- | -- | -- | 4WS*2E10 |
| D07 a) | 4401-07-06 | -- | -- | -- | -- | -- | -- | 4WS2E16 |
| D08 a) | 4401-08-07 | -- | -- | -- | -- | -- | -- | 4WSEE25 |
| D10 a) | 4401-10-08 | -- | -- | -- | -- | -- | -- | 4WSE3EE32 |

a) Daman standard manifolds or subplates may be used. See sections 1 and 4. b) Use D05 servo tapping plate for pilot port, if req'd. See page 101.