

1500 PSI Flow Meters

For Air / Caustic and Corrosive Gases

- Direct reading
- Install in any position
- 360° Rotatable Guard/Scale
- Easier to Read Linear Scale
- No Flow Straighteners or Special Piping Required
- Insensitive to Shock and Vibration
- Temperature up to 240°F
- Accuracy $\pm 2\%$ Full Scale
- Repeatability $\pm 1\%$
- Special Scales Available

SPECIFICATIONS:

MATERIALS:

T316 Stainless body, piston and cone

COMMON PARTS:	Retaining Ring: T316 SS
Spider Plate: T316 SS	Retaining Spring: T316 SS
Spring: T316 SS	Indicator and Internal Magnet: PPS / Ceramic
Fasteners: T316 SS	Bumper: Buna N
Seals: Viton®	Scale Support: 6063 - T6 Aluminum
Guard: Polycarbonate	End Caps: Nylon ST

THREADS: NPTF ANSI B2.2, BSPP ISO1179

TEMPERATURE RANGE: -20 to 240°F (-29 to 116°C) for higher temperatures consult factory

PRESSURE RATING:

Air / Gases Operating: 1,500 psi/103 bar max. with a 10:1 safety factor.

Fatigue Rating: per NFPA T2.6.1R1-1991, (for details see page 7)

PRESSURE DROP: See Ordering Information Table, page 34. For detailed differential pressure charts, see page 55.

ACCURACY: $\pm 2\%$ of full scale reading

REPEATABILITY: $\pm 1\%$

HOSTILE ENVIRONMENT OPTION SPECIFICATIONS:

MATERIALS:

T316 Stainless body, piston and cone

COMMON PARTS:	Retaining Ring: T316 SS
Spider Plate: T316 SS	Retaining Spring: T316 SS
Spring: T316 SS	Indicator: T416 SS
Fasteners: T316 SS	Bumper: T316 SS
Seals: Viton	Scale Support: T316 SS
End Caps: T316 SS	Guard: Cylindrical Pyrex™ glass
Internal Magnet: Teflon Coated Alnico 8	

TEMPERATURE RANGE: -20 to 400°F (-29 to 205°C) Continuous

400 to 500°F (205 to 260°C) Intermittent

For detailed "Pressure vs. Temperature" correlation information, see page 34.


NOTE: See page 29 for dimensions and similar photo illustration.



DIMENSIONS:

A	B	C	D	E	F
NOMINAL PORT SIZE	LENGTH in (mm)	WIDTH in (mm)	DEPTH in (mm)	OFFSET in (mm)	FLATS in (mm)
1/4	4.8 (122)	1.68 (43)	1.90 (48)	.84 (21)	.88 (22)
1/2	6.6 (168)	2.07 (53)	2.40 (61)	1.04 (26)	1.25 (32)
3/4	7.2 (183)	2.48 (63)	2.85 (72)	1.24 (32)	1.50 (38)
1	7.2 (183)	2.48 (63)	2.85 (72)	1.24 (32)	1.50 (38)
1-1/4	12.2 (310)	4.12 (105)	4.72 (120)	2.06 (52)	2.75 (70)
1-1/2	12.2 (310)	4.12 (105)	4.72 (120)	2.06 (52)	2.75 (70)

NOTE: Weights for all sizes can be found on page 57.



1500 PSI Flow Meters

For Air / Caustic and Corrosive Gases

ORDERING INFORMATION:

NOMINAL PORT SIZE	FLOW RANGE		PRESSURE DROP		MODEL NUMBER <i>(see example below*)</i>		HOSTILE ENVIRONMENT OPTION
	① SCFM	② L/SEC	50% FLOW PSI (BAR)	100% FLOW PSI (BAR)	GASES 1.0 (S.G.)		
					NPTF	BSPP	
1/4	2 - 20	1 - 9	6.50 (.45)	12.50 (.86)	H237X - 020 - †	H238X - 020 - †	HE
	3 - 30	1.5 - 14	10.75 (.74)	21.25 (1.47)	H237X - 030 - †	H238X - 030 - †	
1/2	3 - 25	2 - 12	5.63 (.39)	9.38 (.65)	H637X - 025 - †	H638X - 025 - †	HE
	5 - 50	3 - 22	4.38 (.30)	7.50 (.52)	H637X - 050 - †	H638X - 050 - †	
	10 - 100	5 - 47	3.00 (.21)	6.88 (.47)	H637X - 100 - †	H638X - 100 - †	
	15 - 150	7 - 70	8.13 (.56)	18.75 (1.29)	H637X - 150 - †	H638X - 150 - †	
3/4	3 - 25	1.5 - 11.5	2.50 (.17)	4.00 (.28)	H737X - 025 - †	H738X - 025 - †	HE
	5 - 50	2 - 23	1.88 (.13)	3.13 (.22)	H737X - 050 - †	H738X - 050 - †	
	10 - 100	5 - 47.5	2.50 (.17)	4.75 (.33)	H737X - 100 - †	H738X - 100 - †	
	15 - 150	7 - 70	5.63 (.39)	10.94 (.75)	H737X - 150 - †	H738X - 150 - †	
1	3 - 25	1.5 - 11.5	2.50 (.17)	4.00 (.28)	H747X - 025 - †	SEE NOTE	HE
	5 - 50	2 - 23	1.88 (.13)	3.13 (.22)	H747X - 050 - †		
	10 - 100	5 - 47.5	2.50 (.17)	4.75 (.33)	H747X - 100 - †		
	15 - 150	7 - 70	5.63 (.39)	10.94 (.75)	H747X - 150 - †		
1-1/4	20 - 200	10 - 95	2.00 (.14)	3.13 (.22)	H837X - 200 - †	H838X - 200 - †	HE
	40 - 400	20 - 180	3.13 (.22)	5.60 (.39)	H837X - 400 - †	H838X - 400 - †	
	60 - 600	30 - 280	4.38 (.30)	8.75 (.60)	H837X - 600 - †	H838X - 600 - †	
	80 - 800	50 - 350	5.60 (.39)	12.00 (.83)	H837X - 800 - †	H838X - 800 - †	
1-1/2	20 - 200	10 - 95	2.00 (.14)	3.13 (.22)	H847X - 200 - †	SEE NOTE	HE
	40 - 400	20 - 180	3.13 (.22)	5.60 (.39)	H847X - 400 - †		
	60 - 600	30 - 280	4.38 (.30)	8.75 (.60)	H847X - 600 - †		
	80 - 800	50 - 350	5.60 (.39)	12.00 (.83)	H847X - 800 - †		

Note: Consult factory for availability.


① SCFM/PSI multipressure scales are standard.

② L/sec/bar multipressure scales are available at no extra charge. Consult factory for other options.

(example) H 737X - 250 - HE

⚠ **Caution:** When ordering a L/sec/bar scale add "S1" suffix to part number

(example) H737 X - 250 - S1 or H737 X - 250 - HE - S1



AIR & COMPRESSED GASES

PAGE 35



AIR TEST KITS

PAGE 37



FLOW ALERT FLOW SWITCHES

PAGE 39



FLOW TRANSMITTERS

PAGE 41

