



FOR USER/OPERATOR SAFETY
SEE DETAILS PAGE L4

P. T. O. Products



Splined Adaptors – to 75 HP

- ◆ Capacity to operate on tractors related to 75 P.T.O. HP
- ◆ Provide a means of connecting two dissimilar splines
- ◆ Welded steel construction for added strength
- ◆ Corrosion resistant finish
- ◆ Spring and retaining ring pin or setscrews furnished

Female Spline	Male Spline	Length (Inches)	Extends Tractor P.T.O.		Secured By	Part Number
			Shaft End	Shaft Retaining Groove		
25mm-18	1 3/8-6	4 5/8	3 3/8	3 1/2	Cross Pin	0332-00084*
1 1/8-6	1 3/8-6	5 1/2	3 3/4	3 5/8	Cross Pin	0332-03531
1 1/8-6	1 1/8-6	5 1/2	3 3/4	3 5/8	Cross Pin	0332-00377*
1 1/8-6	1 1/8-6	6 1/2	4 3/8	4 1/4	Cross Pin	0332-00400
1 1/8-6	1 1/8-6	5 5/8	3 5/16	3 5/16	Cross Pin	0332-00420
1 1/8-6	1 3/8-6	6 1/2	4 3/8	3 7/8	Cross Pin	0332-00371
1 1/8-6	1 3/8-6	5 5/8	3 5/16	3 5/16	Cross Pin	0332-00378
1 3/8-21	1 3/8-6	6 1/2	4 3/8	3 7/8	Setscrew	0332-00373
1 3/8-21	1 3/4-20	7	5	4 1/2	Setscrew	0332-00070
1 3/8-6	1 3/8-6	6 1/2	4 3/4	4 5/8	Cross Pin	0332-00401

* Manufactured to order



Splined Adaptors – to 125 HP

- ◆ Capacity to operate on tractors related to 125 P.T.O. HP
- ◆ Developed for long and rugged use
- ◆ Alloy steel, heat treated for extra strength
- ◆ Corrosion resistant finish
- ◆ Setscrews furnished

Female Spline	Male Spline	Length (Inches)	Extends Tractor P.T.O.		Secured By	Part Number
			Shaft End	Shaft Retaining Groove		
1 3/8-21	1 3/8-21	6 7/8	4 13/16	4 13/16	Setscrew	0332-00001
1 3/8-21	1 3/8-6	6 7/8	4 13/16	4 11/16	Setscrew	0332-00002
1 3/8-21	1 3/4-20	7 11/64	4 63/64	4 31/64	Clamp Type	0332-00094**
1 3/8-6	1 3/8-21	6 7/8	4 13/16	5 5/16	Setscrew	0332-00004
1 3/8-6	1 3/8-6	6 7/8	4 13/16	5 3/16	Setscrew	0332-00005*

** Not heat treated

* Manufactured to order

Certified prints are available upon request



FOR USER/OPERATOR SAFETY
SEE DETAILS PAGE L4

P. T. O. Products

Kwik-D-Tach Spline Adaptors – to 75 HP

- ◆ Capacity to operate on tractors rated to 75 P.T.O. HP
- ◆ Patented Quick Release Drive
- ◆ New P.T.O. Quick Release Concept – Spring Loaded –rotates about 30° by hand for quick release
- ◆ Dependable operation – no sticking pins. Always easily operated
- ◆ No sharp edges, protrusions, pins or other interferences to injure operators

⊗ See usage safety warning on page L4



Female Spline	Male Spline	Length (Inches)	Extends Tractor P.T.O.		Part
			Shaft End	Shaft Retaining Groove	
1 3/8-6	1 3/8-6	6 1/2	4 3/8	4 3/8	0332-00010
1 3/8-6	1 3/8-21	6 1/2	4 3/8	4 7/8	0332-00013
1 3/8-6	1 1/8-6	6 1/2	4 3/8	4 3/4	0332-00015*
1 3/8-21	1 3/8-6	6 1/2	4 3/8	3 7/8	0332-01373
1 3/8-21	1 3/8-21	6 1/2	4 3/8	4 3/8	0332-02121
Repair Kit					0332-00086

* Manufactured to order

Splined Adaptors – to 75 HP

For tractors with 1 3/4 - 20 Spline P.T.O.

⊗ See usage safety warning on page L4



Female Spline	Male Spline	Length (Inches)	Extends Tractor P.T.O.		Secured By	Part Number
			Shaft End	Shaft Retaining Groove		
1 3/4-20	1 3/8-6	8 3/16	5 3/16	5 3/16	Clamp Type	0332-01476
1 3/4-20	1 3/8-21	8 3/16	5 3/16	5 1/16	Clamp Type	0332-01477

Heavy-Duty Splined Adaptors – to 125 HP

For tractors with 1 3/4 - 20 Spline P.T.O.

⊗ See usage safety warning on page L4



Female Spline	Male Spline	Length (Inches)	Extends Tractor P.T.O.		Secured By	Part Number
			Shaft End	Shaft Retaining Groove		
1 3/4-20	1 3/8-6	8 3/16	5 3/16	5 3/16	Clamp Type	0332-01490
1 3/4-20	1 3/8-21	8 3/16	5 3/16	5 1/16	Clamp Type	0332-01491

Certified prints are available upon request



FOR USER/OPERATOR SAFETY
SEE DETAILS PAGE L4

P. T. O. Products

P.T.O. Products



“Forged” P.T.O. Adaptor – to 75 HP

- ◆ 1 ½ - 6 Spline female — 1 ¾ - 6 Spline male PART NO. 0332-00018
- ◆ “Forged” internal spline
- ◆ Universal quick-detach slot and bolt holes – can be used with any American, British or European P.T.O. system
- ◆ Furnished with 5/16 x 1 1/8 spring pin for direct connection to P.T.O.
- ◆ Overall length: 3 – extends P.T.O. 1 1/8



Push-Pin Type P.T.O. Adaptors – to 75 HP

Quick Release Extension Adaptor

⊗ See usage safety warning on page L4

Female Spline	Male Spline	Length (Inches)	Extends Tractor P.T.O.		Part Number
			Shaft End	Shaft Retaining Groove	
1 ¾-6	1 ¾-21	6 ½	4 ¾	4 7/8	0332-00092
1 ¾-21	1 ¾-6	6 ½	4 ¾	3 7/8	0332-01375
Repair Kit				Old Style	0335-90120
				New Style	0336-00182

Spring Type Release



Round Shaft Adaptors – to 75 HP

Female Round	Keyway	Male Spline	Length	Extends Shaft	Part Number
1	¼	1 ¾-6	5 1/16	3 ¼	0332-00376
1 ½	¼	1 ¾-6	5 1/16	3 3/8	0332-00430
1 ¼	¼	1 ¾-6	5 1/16	3 3/8	0332-00431
1 ¾	5/16	1 ¾-6	5 1/16	3 3/8	0332-00432
1 ½	3/8	1 ¾-6	6 1/2	4	0332-00433



Clamp Type P.T.O. Adaptors – to 75 HP

⊗ See usage safety warning on page L4

Female Spline	Male Spline	Length (Inches)	Extends Tractor P.T.O.		Part Number
			Shaft End	Shaft Retaining Groove	
1 ½-6	1 ¾-6	7 5/8	4 ¾	4 ¾	0332-01354
1 ¾-6	1 ¾-6	7 5/8	4 ¾	4 ¾	0332-00057
1 ¾-21	1 ¾-6	7 5/8	4 ¾	3 7/8	0332-00087



Sleeve Type Splined Adaptors – to 75 HP

Female Spline	Male Spline	Length (Inches)	Part Number	Special Applications
3/8-10	1 ¾-6	2 ¼	0332-00355	IHC Cub & Kubota
1 ½-6	1 ¾-6	2 ¼	0332-00352	
1 ½-6	1 ¾-6	2	0332-00363	Replaced Ford 231082
1 ¾-6	1 ¾-6	2 ½	0332-00403*	

* Manufactured to order

Certified prints are available upon request



FOR USER/OPERATOR SAFETY
SEE DETAILS PAGE L4

Kwik-D-Tach Splined Pump Drive Adaptors

Same safe, dependable, fast action release as Kwik-D-Tach Splined Adaptors

⊗ See usage safety warning on page L4

Female Spline	Female Round*	Keyway	Length(inches)	Part Number
1 3/8-6	.625	3/16 X 3/32	4 1/8	0332-00012
1 3/8-6	.750	3/16 X 3/32	4 1/8	0332-00014
1 3/8-6	.875	3/16 X 3/32	4 1/8	0332-00011
1 3/8-6	.937	1/4 X 1/8	4 1/8	0332-00040
1 3/8-6	1.000	1/4 X 1/8	4 1/8	0332-00016
1 3/8-6	1.125	1/4 X 1/8	4 1/8	0332-00017

* Nominal + .002



Splined Pump Drive Adaptors

1 3/8 - 21 Spline Pump Drives are supplied with setscrews

Female Spline	Female Round*	Keyway	Length(inches)	Part Number
1 3/8-6	1.000	1/4 X 1/8	3 1/16	0332-00412
1 3/8-6	.625	3/16 X 3/32	4 1/8	0332-00407
1 3/8-6	.750	3/16 X 3/32	4 1/8	0332-00408
1 3/8-6	.875	3/16 X 3/32	4 1/8	0332-00409
1 3/8-6	.937	1/4 X 1/8	4 1/8	0332-00413
1 3/8-6	1.000	1/4 X 1/8	4 1/8	0332-00410
1 3/8-6	1.125	1/4 X 1/8	4 1/8	0332-00411
1 3/8-21	.625	3/16 X 3/32	4 1/8	0332-00607
1 3/8-21	.750	3/16 X 3/32	4 1/8	0332-00608
1 3/8-21	.937	1/4 X 1/8	4 1/8	0332-00612
1 3/8-21	1.000	1/4 X 1/8	4 1/8	0332-00610
1 3/8-21	1.125	1/4 X 1/8	4 1/8	0332-00611*

* Nominal + .002



Splined Weld-Ons

Description	Part Number
1 3/8-6 Spline, 5 1/4 Long	0332-00358
1 3/8-6 Spline, 5 1/2 Long	0332-00359
1 3/8-21 Spline, 5 1/2 Long	0332-00019



Quick Release Weld-Ons

⊗ See usage safety warning on page L4

Description	Part Number
1 3/8-21 Spline, 3 5/16 Long	0332-01350*
1 3/8-6 Spline, 3 5/16 Long	0332-01345

* Manufactured to order



Certified prints are available upon request

P.T.O. Products



FOR USER/OPERATOR SAFETY
SEE DETAILS PAGE L4

Over-Running Couplers

HUB CITY Over-Running Couplers provide a safe way to protect operators and machinery where inertia of driven units: e.g. rotary mowers, balers, hay conditioners, etc. can over-run driving source. They take the push out of the driven machine and eliminate the chance of broken or twisted P.T.O. shafts. Over-Running Couplers drive solidly from tractor to driven implement, but over-run smoothly when implement exceeds P.T.O. speeds.



Kwik-D-Tach Tractor Models – to 125 HP

- ◆ Patent applied for – pending serial No. U.S. 465 641 – Canadian 1 117 114
- ◆ Capacity to operate on tractors to 125 P.T.O. HP
- ◆ New P.T.O. Quick Release Concept – Spring Loaded – rotates about 30° by hand for quick release
- ◆ Designed to operate with 1000 RPM P.T.O.'s
- ◆ Installation and lubrication instructions enclosed with each coupler

⊗ See usage safety warning on page L4

Female Spline	Male Spline	Length (Inches)	Extends Tractor P.T.O.		Part Number
			Shaft End	Shaft Retaining Groove	
1 3/8-6	1 3/8-6	7 5/16	4 13/16	5 3/16	0331-00010
1 3/8-6	1 3/8-21	7 3/16	4 11/16	5 3/16	0331-00011
1 3/8-21	1 3/8-6	7 5/16	5 5/16	5 3/16	0331-00012
1 3/8-21	1 3/8-21	7 3/16	5 3/16	5 3/16	0331-00013
Repair Kit					0337-00126



Tractor Models – to 75 HP

Over-Running Couplers covered by Patent No. 3,233,471 – Canadian Patent No. 727-982

- ◆ All steel welded housing
- ◆ Heat treated alloy steel inner sleeve
- ◆ Hardened steel keys, spring loaded
- ◆ Snap ring construction for quick, easy disassembly for cleaning and service
- ◆ Spring roll pin for quick mounting to tractor
- ◆ Convenient grease fitting for gun lubrication
- ◆ Designed to operate with 1000 RPM P.T.O.'s

⊗ See usage safety warning on page L4

Female Spline	Male Spline	Length (Inches)	Extends Tractor P.T.O.		Fits Tractor	Part Number
			Shaft End	Shaft Retaining Groove		
1 1/8-6	1 1/8-6	6 21/32	4 5/32	4 1/32	All with Cross Pin Hole Including Ford	0331-00690
1 1/8-6	1 3/8-6	6 21/32	4 5/32	4 1/32	All with Cross Pin Hole Including Ford	0331-00670
1 1/8-6	1 1/8-6	6 21/32	4 5/32	4 1/32	All with Cross Pin Hole Including Ford	0331-00680
1 1/8-6	1 3/8-6	6 21/32	4 5/32	4 1/32	All with Cross Pin Hole Including Ford	0331-00660
Repair Kit						0337-00076

Installation and lubrication instructions enclosed with each coupler.
For Non-PTO Over-running Couplers, refer to page L15.

Certified prints are available upon request