

D03 to D05 Step-Up Valve Adapters

VA_03G05GUA244
STYLE A**

SECTION A-A

Note for Assembly:
1) Fasten base to D03 manifold with bolts supplied.
2) D05 Threads begin at 1.47" depth from interface surface.

VA_03G05GABU***
D05
T A P B
D03

VA_03G05GBAU***
D05
T A P B
D03

UNC mounting kit includes:
4 - 10-24 x 1.50" SHCS
8 - 012 O-ring viton
2 - Split Pin

Metric mounting kit includes:
4 - M5 x .8 x 35mm SHCS
8 - 012 O-ring viton
2 - Split Pin

VA_03G05GUB444
STYLE B**

SECTION A-A

Note for Assembly:
1) Fasten base to D03 manifold with bolts supplied.
2) D05 Threads begin at 1.47" depth from interface surface.

VA_03G05GABU***
D05
T A P B
D03

VA_03G05GBAU***
D05
T A P B
D03

UNC mounting kit includes:
4 - 10-24 x 3.50" SHCS
8 - 012 O-ring viton
2 - Split Pin

Metric mounting kit includes:
4 - M5 x .8 x 90 mm SHCS
8 - 012 O-ring viton
2 - Split Pin

3

VALVE ADAPTERS

PART NUMBER SYSTEM

TYPE	MATERIAL	MANIFOLD INTERFACE (BOTTOM)	SOLENOID INTERFACE (TOP)	PORT ORIENTATION	MOUNTING HOLES & KIT	STYLE & HEIGHT
VA Valve Adapter		03G ISO 4401-03-02 NFFPA T3.5.1-D03		AB A & B Oriented BA A & B Reversed		A244 Style A - Short Height = 2.44" B444 Style B - Tall Height = 4.44"
	A Aluminum D Ductile Iron		05G ISO 4401-05-04 NFFPA T3.5.1-D05		U UNC Threads and Mounting Kit M Metric Threads and Mounting Kit	

WE RESERVE THE RIGHT TO DISCONTINUE MODELS, OR CHANGE SPECIFICATIONS WITHOUT NOTICE OR INCURRING OBLIGATION

Lynch Products Can Be Modified to Suit Your Application