



# BASIC ELECTRICAL OPTIONS




QUICK CONNECTS - OPTION "QC"  
 • 1/4" MALE SPADES



MALE DIN - OPTION "HH"  
 • DIN 43650-A TYPE  
 • PLUG ONLY


PIN ASSIGNMENTS -  
 #1 COMMON, #2 NORMALLY CLOSED,  
 #3 NORMALLY OPEN, #4 NOT USED




WIRE LEADS - OPTION "WL"  
 • 18 AWG WIRE, 18" LONG




WEATHER PACK - OPTION "WP"  
 • FEMALE "TOWER" TYPE  
 • 18 AWG WIRE  
 • 6" COMPLETE LENGTH




MALE CONDUIT - OPTION "EL"  
 • 1/2" - 14 NPT MALE CONNECTION  
 • INCLUDES "WL" OPTION




METRI-PACK - OPTION "MP"  
 • FEMALE 280 SERIES  
 • 18 AWG WIRE  
 • 6" COMPLETE LENGTH



FEMALE CONDUIT - OPTION "EF"  
 • 1/2" - 14 NPT FEMALE CONNECTION  
 • INCLUDES "WL" OPTION



WATERPROOF MIL CONNECTOR -  
 OPTION "PP"  
 • MS 27412 STYLE  
 • 16 AWG WIRE



COMPLETE DIN - OPTION "HR"  
 • DIN 43650-A TYPE  
 • PLUG AND RECEPTACLE INCLUDED

CABLE CLAMP FOR 18" (4.5 mm) THRU 28" (7 mm) DIA. CABLE  
 PIN ASSIGNMENTS - #1 COMMON, #2 NORMALLY CLOSED,  
 #3 NORMALLY OPEN, #4 NOT USED

## \*COLOR CODE:

BLACK - COMMON  
 RED - NORMALLY OPEN  
 BLUE - NORMALLY CLOSED

## \*\* PIN CONFIGURATION (C CIRCUIT)

A - NORMALLY OPEN  
 B - COMMON  
 C - NORMALLY CLOSED

**HR**