

PRESSURE/VACUUM SWITCH MEDIA CONNECTION DESIGNATIONS

OPTION#	BASE PER OPTION	CM	SM	MM	LM	NS	SP	XM	WS	VM	NV	VP	IS
#1	1/4" - 18 NPT Male	•	•	•	•	•	•	•	•	•	•	•	•
#2	1/8" - 27 NPT Male	•	•	•	•	•	•	•	•	•	•	•	•
#3	3/4" - 16 SAE J514 O-Ring Male (-8)	•	•	•		•		•	•	•	•	•	•
#4	7/16" - 20 SAE J514 37° Flare Male (-4)							•	•		•	•	•
#5	1/4" - 18 NPT Female	•	•	•			•	•	•		•	•	•
#6	7/16" - 20 SAE J514 O-Ring Male (-4)	•	•	•	•	•	•	•	•		•	•	•
#7	1/4" - 18 NPT Female	*OBSOLETE* SEE OPT. 5											
#8	1/8" - 27 NPT Female	•	•	•			•	•	•	•	•	•	•
#9	3/8" - 18 NPT Male						•	•	•		•	•	•
#10	1/4" - Female Stainless Steel	*OBSOLETE* SEE OPT. 5											
#11	9/16" - 18 SAE J514 O-Ring Male (-6)	•	•	•	•		•	•	•	•	•	•	•
#12	M10-1 METRIC	•	•	•									
#13	1/2" - 20 SAE J514 O-Ring Male (-5)	•	•	•			•	•	•	•	•	•	•
#14	1/2" NPT Male/1/8" NPT Female	•	•	•		•							
#15	7/16" - 20 SAE J514 O-Ring Female (-4)							•	•		•	•	•
#16	7/16" - 20 SAE J514 37 DEG				•								
#17	1/4" -19 BSPP (G 1/4") Male	•	•	•	•	•	•	•	•	•	•	•	•
#18	7/16" - 20 SAE J514 O-Ring Male ADJ (-4)							•	•		•	•	•
#19	1/8" - 28 BSPT (R 1/8") Male	•	•	•			•	•	•		•	•	•
#20	1-1/2" Pipe Sanitary Connection					•		•	•		•	•	•
#21	1/4" BSPP Extended (G 1/4)	•	•	•				•	•	•	•	•	•
#22	1/2" - 14 NPT Brass Male (IS Only)							•	•		•	•	•
#23	1/4" - 18 NPT SS Female (IS Only)							•	•		•	•	•
#24	3/8"- 24 UNF Male/10-32 UNF Female	•	•	•									
#25	1/4" - 18 NPT Male Nylon	*OBSOLETE* SEE OPT. 1											
#26	9/16" - 18 SAE J514 37° Flare Female (-6)							•	•		•	•	•
#27	1/2" - 14 BSPT (R 1/2") Male	•	•	•						•			
#28	1/8" - 28 BSPP (G 1/8") Male	•	•	•									
#29	3/8" - 24 SAE J514 O-Ring Male (-3)	•	•	•				•	•		•	•	•
#30	1/4" - 19 BSPT (R 1/4) Male	•	•	•						•			

Note: Consult factory for materials and stock

PRESSURE/VACUUM SWITCH MEDIA CONNECTION DESIGNATIONS

OPTION#	BASE PER OPTION	CM	SM	MM	LM	NS	SP	XM	WS	VM	NV	VP	IS
#31	Flange					•							
#32	M12-1.5 METRIC	•	•	•				•	•		•	•	•
#33	Extended Flange					•							
#34	7/16" - 20 MS33649 Female (-4)					•							
#35	1/2" - 14 NPT Male					•		•	•	•	•	•	•
#36	9/16" -18 SAE J514 Extended Boss O-Ring Male (-6)				•								
#37	3/8" - 24 Inverted Flare	•	•	•									
#38	Special SR					•		•	•	•	•	•	•
#39	1/4" -18 NPT SAE J516 Hose Male (-4)							•	•		•	•	•
#40	M 10x1 SAE J2244-3 O-Ring Male	•	•	•									
#41	7/16" -20 Internal 45 Degree Flare -SAE J 513	•	•	•						•			
#42	9/16" -18 ADJ												
#43	M10x1 SAE J2244-3 Extnd.	•	•	•									
#44	1/4" -18 NPT Female Ext.							•	•		•	•	•
#45	9/16" -18 SAE O-Ring							•	•		•	•	•
#46	1/8" - NPT Male Clipped NEX	•	•	•									
#47	1/4" -19 BSPP Female (G1/4)							•	•		•	•	•
#48	9/16" -18 SAE Male 1/8 NPT									•			
#49	M14x1.5 J2244/3	•	•	•									
#50	.302-32 Female	•	•	•									
#51	M14x1.5 (19mm HEX)				•								
#52	3/8" - UNF w/1/4" BARB	•	•	•									
#53	3/8" - M12x1.5 SAE J2244				•			•	•		•	•	•

Note: Consult factory for materials and stock