

**Introduction**

Manapak valves provide a variety of check, flow control, pressure relief and pressure reducing functions in a compact NFPA D03, D05 and D08 sandwich style valve. The NFPA D03 valve body conforms to the ISO 40 mm (1.57") thickness. These valves are mounted between directional control valves and their mounting surface.


The NFPA D03 Manapak valves may also be used in conjunction with Parker's Cartpak Series of sandwich valves which offer a wide variety of additional functions including relief, pressure reducing/relieving, load check, back pressure check, needle, flow control, pressure compensated flow control, crossover, relief and directional valves.

**B**


**Check Valves**

**Series CM**

- Valve bodies are manufactured from steel which provide extra strength and durability for longer life. Internal hardened steel components also provide longer life.
- Positive shut-off is provided by a fully guided poppet and allows full flow in the unchecked position.
- Parker Manapak CM sandwich style check valves can be used either on the 'P', 'A', 'B', 'T' port or combination.
- Large internal flow paths allow high flow at low pressure drop.




**CM\*PT**




**CM\*AA**




**CM\*AAF**




**CM\*BB**




**CM\*BBF**




**CM\*DD**




**CM\*DDF**



**CM\*PP**




**CM\*TT**




**P. O. Check Valves**

**Series CPOM**


- Parker Manapak CPOM sandwich style, pilot operated check valves can be provided in either single or double configurations.
- The pilot operated checks may be positioned in 'A' port or 'B' port; or both 'A' and 'B' ports.
- Valve bodies are manufactured from steel which provide extra strength and durability for longer life. Internal hardened steel components also provide longer life.
- Positive shut-off is provided by a hardened poppet and cage assembly.
- Large internal flow paths allow high flow at low pressure drop.




**CPOM\*AA**



**CPOM\*BB**



**CPOM\*DD**




**Flow Control Valves**

**Series FM**

- Parker Manapak style FM flow control valves can be provided in either single or double configurations.


The flow controls may be positioned in 'P' port, 'A' port, 'B' port, or both 'A' and 'B' ports.

- Valve bodies are manufactured from steel which provide extra strength and durability for longer life. Internal hardened steel components also provide longer life.
- Two step needles (standard) provide fine adjustment for the first three turns and course adjustment for the last three turns. Fine metering needles are available as an option.
- Large bypass checks allow high flow at a low pressure drop.
- Reversible (invert 180°) for meter-in or meter-out (D03 & D05 only).




**FM\*AA**

(Meter Out)




**FM\*BB**

(Meter Out)




**FM\*DD**

(Meter Out)



**FM\*PP**


(Meter Out)




**Pressure Reducing Valves**

**Series PRDM**


- PRDM Manapak sandwich valves may be selected to reduce pressure in the 'P' port, 'A' port or 'B' port.
- The direct operated, cushioned piston design results in fast response, low leakage and minimal hysteresis.
- Up to four pressure adjustment ranges are available with maximum pressure settings of 25, 64, 160 and 210 Bar (363, 928, 2320, 3045 PSI).
- Adjustment options include: internal hex screw, hand knob or internal hex with keylock.
- Fluorocarbon seals are standard for multi-fluid compatibility.
- Available gage port connections include: SAE, NPT, BSPP Metric and ISO 6149.




**PRDM\*PP**



**PRDM\*AA**




**PRDM\*BB**



**Pressure Reducing Valves**

**Series PRM**


- Parker Manapak PRM sandwich style pressure reducing valves can be used to reduce pressure on the 'P' port, the 'A' port, or the 'B' port.
- Three pressure adjustment options available: slotted screw, knob and locking knob.
- Valve bodies are manufactured from steel which provide extra strength and durability for longer life. Internal hardened steel components also provide longer life.




**PRM\*AA**



**PRM\*BB**




**PRM\*PP**




**Pressure Relief Valves**

**Series RM**

- Parker Manapak RM sandwich style relief valve is a 'P' port to 'T' port relief.
- Valve bodies are manufactured from steel which provide extra strength and durability for longer life. Internal hardened steel components also provide longer life.
- Three pressure adjustment options available: slotted screw, knob and locking knob.



**RM\*PT**



**General Description**





The CPOM series of double pilot operated check valves blocks leakage from the actuator ports to tank when the directional valve is in the center position.

**NOTE:** For max. response and shut off, a directional valve with both cylinder ports drained to tank in the center position is recommended for use with Manapak double pilot operated check valves.

**Features**


- Parker Manapak CPOM sandwich style, p.o. check valves can be provided in either single or double configurations.
- The p.o. checks may be positioned in 'A' port or 'B' port; or both 'A' and 'B' ports.
- Valve bodies are manufactured from steel providing extra strength and durability for longer life. Internal hardened steel components also provide longer life.
- Positive shut-off is provided by a hardened poppet and cage assembly.
- Large internal flow paths allow high flow at low pressure drop.

**Performance Curves**



**Specifications**

	<b>CPOM2</b>	<b>CPOM3</b>	<b>CPOM6</b>
<b>Mounting Pattern</b>	NFPA D03, CETOP 3, NG 6	NFPA D05, CETOP 5, NG 10	NFPA D08, CETOP 8, NG 25
<b>Maximum Pressure</b>	345 Bar (5000 PSI)	345 Bar (5000 PSI)	345 Bar (5000 PSI)
<b>Maximum Flow</b>	53 LPM (14 GPM) @ 21 Bar (305 PSI) Pressure Drop	76 LPM (20 GPM) @ 11 Bar (155 PSI) Pressure Drop	227 LPM (60 GPM) @ 24 Bar (350 PSI) Pressure Drop
<b>Cracking Pressure</b>	0.3 Bar (5 PSI)	0.3 Bar (5 PSI)	0.3 Bar (5 PSI)
<b>Pilot Ratio</b>	3:1	3:1	3:1



Curves were generated using 100 SSU hydraulic oil. For any other viscosity, pressure drop will change as per chart.	<b>Viscosity Correction Factor</b>							
	Viscosity (SSU)	75	150	200	250	300	350	400
	Percentage of ΔP (Approx.)	93	111	119	126	132	137	141

2502-B1.p65, dd



**CPOM**

Manapak  
 Double Pilot  
 Operated  
 Check Valve

Size

Poppet  
 Style

Poppet  
 Style

Cracking  
 Pressure

Cracking  
 Pressure

**V**

Seal

**\***

Design  
 Series  
 NOTE:  
 Not required  
 when ordering.

Code	Description
2	NFPA D03 Subplate Mounting
3	NFPA D05 Subplate Mounting
6	NFPA D08 Subplate Mounting

Code	Description
DD	Double Poppet A and B Ports
AA	A Port Only
BB	B Port Only

Code	Type
Omit	5 PSI
Y	45 PSI
Z	75 PSI

Code	Type
V	Fluorocarbon

**B**

**Manapak Bolt Kits**

Size "2"				Size "3"			
No. of Manapaks	Manapak & Valve Combination	Bolt Kit	Bolt Length mm (in)	No. of Manapaks	Manapak & Valve Combination	D3W-30 D3DW & D31VW*	Bolt Length mm (in)
1	Manapak & D1	BK243	73.2 (2.88)	1	Manapak & D3	BK141	88.9 (3.50)
2	Manapak & D1	BK225	111.3 (4.38)	2	Manapak & D3	BK142	139.7 (5.50)
3	Manapak & D1	BK244	152.4 (6.00)	3	Manapak & D3	BK143	190.5 (7.50)
4	Manapak & D1	BK245	190.5 (7.50)				

\* D31VW with internal pilot and internal drain only.


Size "6"			
No. of Manapaks	Manapak & Valve Combination	Bolt Kit	Bolt Length mm (in)
1	Manapak & D6	BK121	133.4 (5.25)
2	Manapak & D6	BK122	203.2 (8.00)
3	Manapak & D6	BK123	273.1 (10.75)
4	Manapak & D6	BK124	342.9 (13.5)

**Unit Weight:**


CPOM2D	0.8 kg (1.7 lbs.)
CPOM3D	4.4 kg (9.6 lbs.)
CPOM6D	9.5 kg (21.0 lbs.)

Bolt Kits must be ordered separately.


**Schematics**



AA Option



BB Option




DD Option

**B**

**CAUTION:**  
**Manapak Installation**

Prior to installation of Manapaks, please review flow paths. Due to the reversibility of the DO3 size, incorrect installation will alter the hydraulic circuit. Care must be taken during installation to insure that the Manapak is installed in compliance with the hydraulic schematic. Please consult with your Parker representative with any questions that may arise.



**Pressure Ratings**

Unless otherwise specified, all Parker Manapaks have continuous duty pressure rating as shown in this catalog.

**Special Requirements**

Consult your Parker representative for factory recommendations on such situations as:

- Installations that will operate at pressures higher than published catalog ratings.
- Use of hydraulic fluids which do not meet our recommended specifications.
- Operations where fluid temperature will exceed 121°C (250°F).

**Recommended Mounting Surface**

Surface must be flat within .0004 inch T.I.R. and smooth with 32 micro-inch.

**System Cleanliness**

Any hydraulic system that includes Parker valves should be carefully protected against dirt and fluid contamination. Life of the valves, as well as of all other components, will be greatly lengthened. Operation will be smoother and more precise. Maintenance and repairs will be reduced. Lost production because of low pressure and flow will be minimized. Fluid contamination should be maintained to less than 500 particles larger than 10 micrometers per milliliter of fluid (SAE class 4 or better/ISO Code 16/13).

**Hydraulic Fluids**

Parker recommends using top-quality hydraulic fluids having a viscosity range of 150 to 250 SSU (32 to 54 cst.) at 38°C (100°F). The absolute viscosity range should be 80 to 1000 SSU (16 to 220 cst.). Fluids should have highest anti-wear characteristics and be treated to avoid rust and oxidation.

**Seals**

When used with water-glycol, water/oil emulsions, and high-grade petroleum base hydraulic fluids, Parker standard nitrile seals are suitable.


When using phosphate ester fluids or their blends, specify Parker optional seals made of fluorocarbon. Synthetic fire-resistant fluids require special seal materials which your Parker representative can recommend.

**Torque Specifications**


The recommended torque valves are for the bolts which mount the valve to the manifold or subplate are as follows:

Size	Torque Valve
2	5.7 N.m. (50 in.-lbs.)
3	16.3 N.m. (12 ft.-lbs.)
6	108.5 N.m. (80 ft.-lbs.)

**Mounting Patterns**




**Mounting Surface for Directional Control Valve Manifold M'TD. (NFPA, D03); CETOP 3 & NG 6**



**Mounting Surface for Directional Control Valve (NFPA, D05); CETOP 5 & NG 10**

**Mounting Patterns**

**B**



**Mounting Surface for Directional Control Valve (NFPA, D08); CETOP 8 & NG 25**