

Special Feature Letter	Location	8000 - 8100	8200	8400	8500	8700	8900	SL-8				
		$\frac{1}{8} - \frac{1}{2}$	$\frac{3}{4} - 1$	$1\frac{1}{4} - 1\frac{1}{2}$	$\frac{1}{8} - \frac{1}{2}$	$\frac{3}{4} - 1$	$\frac{1}{8} - \frac{1}{4}$	$\frac{1}{8} - \frac{1}{2}$	$\frac{3}{4} - 1$	$\frac{1}{8} - \frac{1}{2}$	$\frac{1}{4} - 1$	$1\frac{1}{4} - \frac{3}{8}$
F	-Fourth Seal	P	A	A	A	A	N/A	A	A	N/A	A	A
FR	-Fourth Seal & Spring Return	P	A	A	A	N/A	N/A	N/A	A	A	N/A	N/A
R	-Spring Return	P	A	A	A	N/A	N/A	A	A	A	A	N/A
XR	-Heavy Duty Spring Return	P	A	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
CR	-Normally Closed Spring Return	P	A	A	A	N/A	N/A	N/A	A	A	N/A	N/A
N	-Non Interflow	P	A	N/A	N/A	A	N/A	N/A	A	N/A	A	N/A
NR	-Non Interflow & Spring Return	P	A	N/A	N/A	N/A	N/A	N/A	A	N/A	A	N/A
S	-Delrin Seals	P	N/A	N/A	N/A	N/A	N/A	A	A	A	A	N/A
Z	-Zerk Fitting	P	A	A	A	A	A	N/A	A	A	N/A	A
G	-Panel Mtg.	S	A	A	A	A	A	A	A	A	A	A
C	-Clevis Handle	S	A	A	N/A	A	A	N/A	N/A	A	N/A	N/A
D	-Aluminum Handle	S	A	A	A	N/A	N/A	A	N/A	A	A	N/A
H	-Less Handle	S	A	A	A	A	A	A	A	A	A	A
P	-Locking Kit	S	A	A	N/A	N/A	N/A	N/A	A	N/A	N/A	N/A
L	-No Left Handle Position	S	A	A	A	A	A	N/A	A	A	N/A	A
R	-No Right Handle Position	S	A	A	A	A	A	N/A	A	A	N/A	A
M	-No Center Detent	S	A	A	A	A	A	A	A	A	A	A
N	-Non Detented Valve	S	A	A	A	A	A	A	A	A	A	N/A
V	-Case Drain	S	A	A	A	A	A	N/A	A	A	N/A	N/A
K	-Round Knob Handle	S	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	A	N/A
LB	-Angle Bracket	S	N/A	N/A	N/A	N/A	N/A	N/A	A	N/A	A	N/A
SB	-Straight Bracket	S	N/A	N/A	N/A	N/A	N/A	N/A	A	N/A	A	N/A
HE	-Handle Over Exhaust Port	S	A	A	A	N/A	N/A	A	A	A	A	A

P=Prefix S=Suffix A=Available N/A=Not Available



OPTIONAL VALVE MOUNTING BRACKETS
(For 8500 Series)

Combined Options Not Available

1. Cast Alum. Handle (D) and Clevis Handle (C).
2. Case Drain (V) not available with 0, 1, 5, 8, & T flow patterns.
3. Options M, L & R available individually only.
4. Options FR & NR limits maximum pressure on valve to 1500 PSI.
5. Option FNR not available.
6. Option N not available on 3/4, 1, 1-1/4, & 1-1/2 valves.

